


Poleas Dentadas Métricas

TK

FIGURASYDIMENSIONES



MATERIAL
de 25 a Ø dientes
Aluminio

TK5K6	Referencia	Nº dientes	R Ø (mm)	S Ø (mm)	G (mm)	T (mm)	d Ø (mm)	55-TK5K6	
								Anchocorrea=50mm	
								W (mm)	
	TK5K6/ 25	25	39,79	38,95	6,5	5	8	55	
	TK5K6/ 27	27	42,97	42,13	6,5	5	8	55	
	TK5K6/ 30	30	47,75	46,91	6,5	5	8	55	
	TK5K6/ 32	32	50,93	50,09	6,5	5	8	55	
	TK5K6/ 36	36	57,30	56,46	6,5	5	8	55	
	TK5K6/ 40	40	63,66	62,82	6,5	5	12	55	
	TK5K6/ 48	48	76,39	75,55	6,5	5	12	55	
	TK5K6/ 60	60	95,49	94,65	6,5	5	12	55	

TK10K6	Referencia	Nº dientes	R Ø (mm)	S Ø (mm)	G (mm)	T (mm)	d Ø (mm)	30-TK10K6		55-TK10K6	
								Anchocorrea=25mm		Anchocorrea=50mm	
								W (mm)		W (mm)	
	TK10K6/ 20	20	63,66	61,80	6,5	5	12	30		55	
	TK10K6/ 24	24	76,39	74,55	6,5	5	12	30		55	
	TK10K6/ 25	25	79,58	77,75	6,5	5	12	30		55	
	TK10K6/ 27	27	85,94	84,10	6,5	5	12	30		55	
	TK10K6/ 30	30	95,49	93,65	6,5	5	12	30		55	
	TK10K6/ 32	32	101,86	100,00	6,5	5	12	30		55	
	TK10K6/ 36	36	114,59	112,75	6,5	5	16	30		55	
	TK10K6/ 40	40	127,32	125,45	6,5	5	16	30		55	
	TK10K6/ 48	48	152,79	150,95	6,5	5	16	30		55	
	TK10K6/ 60	60	190,99	189,15	6,5	5	16	30		55	

TK10K13	Referencia	Nº dientes	R Ø (mm)	S Ø (mm)	G (mm)	T (mm)	d Ø (mm)	55-TK10K6		105-TK10K6	
								Anchocorrea=50mm		Anchocorrea=100mm	
								W (mm)		W (mm)	
	TK10K13/ 20	20	63,66	61,80	13,5	7,5	12	55		105	
	TK10K13/ 24	24	76,39	74,53	13,5	7,5	12	55		105	
	TK10K13/ 25	25	79,58	77,72	13,5	7,5	12	55		105	
	TK10K13/ 27	27	85,94	84,10	13,5	7,5	12	55		105	
	TK10K13/ 30	30	95,49	93,63	13,5	7,5	12	55		105	
	TK10K13/ 32	32	101,86	100,00	13,5	7,5	12	55		105	
	TK10K13/ 36	36	114,59	112,73	13,5	7,5	16	55		105	
	TK10K13/ 40	40	127,32	125,46	13,5	7,5	16	55		105	
	TK10K13/ 48	48	152,79	150,93	13,5	7,5	16	55		105	
	TK10K13/ 60	60	190,99	189,13	13,5	7,5	16	55		105	

véasecorreasTK5K6enpágina91

véasecorreasTK10K6enpágina92

véasecorreasTK10K13enpágina93

DINAMICADistribuciones, sa
BARCELONA-MADRID-BILBAO-OURENSE
Tel.:902198131 - dinamica@dinamica.net - www.dinamica.net

